

WHAT IS CLAIMED IS:

Sub
A1

5

1. A closure device comprising:
 a first fastening strip;
 a second fastening strip;
 a slider adapted to be slidably disposed on said
 fastening strips and facilitating the occlusion of said
 fastening strips when moved towards a first end thereof
 10 and facilitating the deocclusion of said fastening strips
 when moved towards a second end thereof, said fastening
 strips and said slider having a longitudinal X axis and a
 transverse Y axis, said transverse Y axis being
 perpendicular to said longitudinal X axis, said fastening
 15 strips and said slider having a vertical Z axis, said
 vertical Z axis being perpendicular to said longitudinal X
 axis, said vertical Z axis being perpendicular to said
 transverse Y axis, a first detent at said first end of
 said fastening strips, said slider comprising a housing
 20 having a protrusion for engaging said first detent of
 said fastening strips when said slider is moved to said
 first end of said fastening strips thereby preventing
 removal of said slider from said first end of said
 fastening strips in said longitudinal X axis.

25

2. The invention as in claim 1, wherein said
 protrusion comprises a peg extending inwardly in the
 transverse Y axis.

30

3. The invention as in claim 1 wherein said
 fastening strips have a first position when the
 protrusion engages the first detent and a second position
 when the protrusion is not engaged with the first detent.

35

4. The invention as in claim 3 wherein the first
 position is deflected from the second position.

00070534 44001

5. The invention as in claim 4 wherein said housing has a void opposite the protrusion to allow the fastening strips to deflect.

Sub A2 5
6. The invention as in claim 5 wherein a first occlusion member is located on one side of the void and a second member is located on the other side of the void.

7. The invention as in claim 6 wherein a second
10 occlusion member is located opposite the first occlusion member.

Sub A3 15
8. The invention as in claim 1 further comprising a second detent at said second end of said fastening strips, said protrusion engaging said second detent when the slider is moved to said second end of said fastening strips thereby preventing removal of said slider from said second end of said fastening strips in said longitudinal X axis.

20
9. The invention as in claim 8 wherein said fastening strips have a first position when the protrusion engages the second detent and a second position when the protrusion is not engaged with the second detent.

25
10. The invention as in claim 9 wherein the first position is deflected from the second position.

Sub A4 30
11. The invention as in claim 1 wherein said housing having a separator to facilitate the occlusion of said fastenings trips.

12. The invention as in claim 11 wherein said separator has a separator axis, said separator axis is
35 parallel to the longitudinal X axis.

13. ~~The invention as in claim 11 wherein said separator has a separator axis, said separator axis is at an angle to the longitudinal X axis.~~

5 14. The invention as in claim 1 wherein said housing having shoulders to engage the fastening strips.

15 15. The invention as in claim 14 wherein said shoulders have shoulder axis, said shoulder axis is parallel to the longitudinal X axis.

15 16. The invention as in claim 14 wherein said shoulders have shoulder axis, said shoulder axis is at an angle to the longitudinal X axis.

15 17. The invention as in claim 12 wherein said housing having shoulders to engage the fastenings strips, said shoulders have a shoulder axis, said shoulder axis is parallel to the longitudinal X axis.

20 18. ~~The invention as in claim 13 wherein said housing having shoulders to engage the fastening strips, said shoulders have a shoulder axis, said shoulder axis is at an angle to longitudinal X axis.~~

25

19. The invention as in claim 18 wherein the shoulder axis is parallel to the separator axis.

30 20. The invention as in claim 1, wherein said fastening strips comprise U-channel closure type fastening strips.

35 21. The invention as in claim 1, wherein said fastening strips comprise arrowhead type fastening strips.

22. The invention as in claim 1, wherein said fastening strips comprise profile type fastening strips.

23. The invention as in claim 1 wherein said fastening strips comprise rolling action fastening strips.

5
Sub
All

24. A slider adapted to be slidably disposed on a first and second fastening strip wherein a first detent is provided at a first end of said fastening strips, said slider facilitating the occlusion of said fastening strips
10 when moved towards said first end thereof and facilitating the deocclusion of said fastening strips when moved towards said second end thereof, said slider comprising:

15 a longitudinal X axis and a transverse Y axis, said transverse Y axis being perpendicular to said longitudinal X axis, said slider having a vertical Z axis, said vertical Z axis being perpendicular to said longitudinal X axis, said vertical Z axis being perpendicular to said transverse Y axis;

20 a housing having a protrusion for engaging said first detent of said fastening strips when said slider is moved to said first end of said fastening strips, said protrusion thereby preventing removal of said slider from said first end of fastening strips in said longitudinal X
25 axis.

25. The invention as in claim 24, wherein said protrusion comprises a peg extending inwardly in the transverse Y axis.

30 26. The invention as in claim 24 wherein said fastening strips have a first position when the protrusion engages the first detent and a second position when the protrusion is not engaged with the first detent.

35 27. The invention as in claim 26 wherein the first position is deflected from the second position.

28. ~~The invention as in claim 27 wherein said housing has a void opposite the protrusion to allow the fastening strips to deflect.~~

5
Sub A7 29. ~~The invention as in claim 28 wherein a first occlusion member is located on one side of the void and a second member is located on the other side of the void.~~

10 30. The invention as in claim 29 wherein a second occlusion member is located opposite the first occlusion member.

15 31. The invention as in claim 24 further comprising a second detent at said second end of said fastening strips, said protrusion engaging said second detent when the slider is moved to said second end of said fastening strips thereby preventing removal of said slider from said second end of said fastening strips in said longitudinal X
20 axis.

32. The invention as in claim 31 wherein said fastening strips have a first position when the protrusion engages the second detent and a second position when the
25 protrusion is not engaged with the second detent.

33. The invention as in claim 32 wherein the first position is deflected from the second position.

30 Sub A8 34. ~~The invention as in claim 24 wherein said housing having a separator to facilitate the occlusion of said fastenings trips.~~

35 35. The invention as in claim 34 wherein said separator has a separator axis, said separator axis is parallel to the longitudinal X axis.

36. ~~The invention as in claim 34 wherein said separator has a separator axis, said separator axis is at an angle to the longitudinal X axis.~~

5 37. The invention as in claim 24 wherein said housing having shoulders to engage the fastening strips.

38. The invention as in claim 37 wherein said shoulders have shoulder axis, said shoulder axis is
10 parallel to the longitudinal X axis.

39. The invention as in claim 37 wherein said shoulders have shoulder axis, said shoulder axis is at an angle to the longitudinal X axis.

15 40. The invention as in claim 35 wherein said housing having shoulders to engage the fastenings strips, said shoulders have a shoulder axis, said shoulder axis is parallel to the longitudinal X axis.

20 41. ~~The invention as in claim 36 wherein said housing having shoulders to engage the fastening strips, said shoulders have a shoulder axis, said shoulder axis is at an angle to longitudinal X axis.~~

25 42. The invention as in claim 41 wherein the shoulder axis is parallel to the separator axis.

30 43. A container comprising:
first and second side walls, said first and second side walls including mating first and second fastening strips respectively, said first and second fastening strips comprising a closure device arranged to be interlocked over a predetermined length,
35 a slider adapted to be slidably disposed on said fastening strips and facilitating the occlusion of said fastening strips when moved towards a first end thereof

and facilitating the deocclusion of said fastening strips when moved towards a second end thereof, said fastening strips and said slider having a longitudinal X axis and a transverse Y axis, said transverse Y axis being

5 perpendicular to said longitudinal X axis, said fastening strips and said slider having a vertical Z axis, said vertical Z axis being perpendicular to said longitudinal X axis, said vertical Z axis being perpendicular to said transverse Y axis, a first detent at said first end, said
10 slider comprising a housing having a protrusion for engaging said first detent of said fastening strips when said slider is moved to said first end of said fastening strips thereby preventing removal of said slider from said first end of said fastening strips in said
15 longitudinal X axis.

44. The invention as in claim 43, wherein said protrusion comprises a peg extending inwardly in the transverse Y axis.

20 45. The invention as in claim 43 wherein said fastening strips have a first position when the protrusion engages the first detent and a second position when the protrusion is not engaged with the first detent.

25 46. The invention as in claim 45 wherein the first position is deflected from the second position.

30 47. The invention as in claim 46 wherein said housing has a void opposite the protrusion to allow the fastening strips to deflect.

35 48. The invention as in claim 47 wherein a first occlusion member is located on one side of the void and a second member is located on the other side of the void.

100777-12362600

Sub
All

49. The invention as in claim 48 wherein a second occlusion member is located opposite the first occlusion member.

Sub 5
A12

50. ~~The invention as in claim 43 further comprising a second detent at said second end of said fastening strips, said protrusion engaging said second detent when the slider is moved to said second end of said fastening strips thereby preventing removal of said slider from said~~
10 ~~second end of said fastening strips in said longitudinal X~~
~~axis.~~

51. The invention as in claim 50 wherein said fastening strips have a first position when the protrusion
15 engages the second detent and a second position when the protrusion is not engaged with the second detent.

52. The invention as in claim 51 wherein the first position is deflected from the second position.

Sub 20
A13

53. ~~The invention as in claim 43 wherein said housing having a separator to facilitate the occlusion of~~
~~said fastenings trips.~~

25 54. The invention as in claim 53 wherein said separator has a separator axis, said separator axis is parallel to the longitudinal X axis..

30 55. The invention as in claim 53 wherein said separator has a separator axis, said separator axis is at an angle to the longitudinal X axis.

56. The invention as in claim 43 wherein said housing having shoulders to engage the fastening strips.

35

57. The invention as in claim 56 wherein said shoulders have shoulder axis, said shoulder axis is parallel to the longitudinal X axis.

5 58. The invention as in claim 56 wherein said shoulders have shoulder axis, said shoulder axis is at an angle to the longitudinal X axis.

59. The invention as in claim 54 wherein said
10 housing having shoulders to engage the fastenings strips, said shoulders have a shoulder axis, said shoulder axis is parallel to the longitudinal X axis.

60. The invention as in claim 55 wherein said
15 housing having shoulders to engage the fastening strips, said shoulders have a shoulder axis, said shoulder axis is at an angle to longitudinal X axis.

61. The invention as in claim 60 wherein the
20 shoulder axis is parallel to the separator axis.

62. The invention as in claim 43, wherein said fastening strips comprise U-channel closure type fastening strips.

25 63. The invention as in claim 43, wherein said fastening strips comprise arrowhead type fastening strips.

64. The invention as in claim 43, wherein said
30 fastening strips comprise profile type fastening strips.

65. The invention as in claim 43 wherein said fastening strips comprise rolling action fastening strips.

Sub
A14 35 ~~66. A method for using a closure device comprising the steps of:
providing a first fastening strip;~~

providing a second fastening strip;
 providing a slider adapted to be slidably disposed
 on said fastening strips and facilitating the occlusion
 of said fastening strips when moved towards a first end
 5 thereof and facilitating the deocclusion of said
 fastening strips when moved towards a second end thereof,
 said fastening strips and said slider having a
 longitudinal X axis and a transverse Y axis, said
 transverse Y axis being perpendicular to said longitudinal
 10 X axis, said fastening strips and said slider having a
 vertical Z axis, said vertical Z axis being perpendicular
 to said longitudinal X axis, said vertical Z axis being
 perpendicular to said transverse Y axis, a first detent at
 said first end of said fastening strips, said slider
 15 comprising a housing having a protrusion for engaging
 said first detent of said fastening strips when said
 slider is moved to said first end of said fastening
 strips thereby preventing removal of said slider from
 said first end of said fastening strips in said
 20 longitudinal X axis;
 moving said slider towards said first end and said
~~protrusion engaging said first detent.~~

67. The invention as in claim 66, wherein said
 25 protrusion comprises a peg extending inwardly in the
 transverse Y axis.

68. ~~The invention as in claim 66 wherein said~~
~~fastening strips have a first position when the~~
 30 ~~protrusion engages the first detent and a second position~~
~~when the protrusion is not engaged with the first detent.~~

69. ~~The invention as in claim 68 wherein the first~~
~~position is deflected from the second position.~~

35

70. The invention as in claim 69 wherein said housing has a void opposite the protrusion to allow the fastening strips to deflect.

Sub
A15 5
71. The invention as in claim 66 further providing a second detent at said second end of said fastening strips, said protrusion engaging said second detent when the slider is moved to said second end of said fastening strips thereby preventing removal of said slider from said
10 second end of said fastening strips in said longitudinal X
axis.

Add
A16

00070524 11071
FOOT: 12502000